ZEOPLUS AXIS INDIA PVT. LTD.

ZEOFINE

ELECTRIC VEHICLES

DRIVE THE FUTURE OF MOBILITY

ZEOFINE

SMART MOBILITY • HIGH MILEAGE • STRONG PERFORMANCE



ZEOFINE E- VEHICLES

ZEOEPOWER@GMAIL.COM

HTTPS://WWW.ZEOFINE.IN/

HTTPS://WWW.FACEBOOK.COM/ZEOFINEERICKSHAWS

ZEOFINE.ERICKSHAW

ZEOFINE DELUXE

SMART MOBILITY • HIGH PERFORMANCE

HIGH MILEAGE
UP TO 150–200 KM PER CHARGE

HEAVY DUTY TYRES
WITH ALLOW WHEEL

BETTER GRADEABILTY
SMOOTH PERFORMANCE ON SLOPES

HIGHER SPEED
POWERFUL MOTOR PERFORMANCE

EASY HOME CHARGING
CHARGE ANYWHERE WITH STANDARD POWER

LOW RUNNING COST
SAVE MORE EVERY DAY

COMFORT SEATING
SPACIOUS PASSENGER SEATING

FINANCE AVAILABLE
EASY LOAN OPTIONS



ZEOFINE – DRIVE THE FUTURE OF MOBILITY

ZEOPLUS LOADER

HIGH LOAD CAPACITY

DESIGNED FOR TRANSPORTING GOODS EASILY

STRONG METAL BODY

DESIGNED FOR TRANSPORTING GOODS EASILY





HALF BODY LOADER

DRIVER + 500 KG LOAD CAPACITY

EXPAND YOUR BUSINESS POSSIBILITIES

EXTRA LOAD SPACE • EXTRA EARNINGS

ZEOPLUS SPEED L5 CATEGORY

DRIVE WITH STYLE, EFFICIENCY & COMFORT

EFFICIENT PERFORMANCE

SAFE & RELIABLE



LONG LIFE BATTERY

PREMIUM COMFORT

1500-1800W

60V

42" WIDTH

4.00 - 12

38 KM/H

Innovation • Service • Excellence

D+6 APPROVED

ZEOPLUS LI

Smart Mobility... Happier Tomorrow!

High Mileage

Long Life Battery



1250 W

105 AH 51.2

3.75 -12 CEAT

ZEOFINE – SMART MOBILITY FOR A BETTER FUTURE

ZEOFINE
Smart Delivery Partner

ZEOPLUS FULL BODY LOADER











5 POWER FEATURES

- High Performance Motor
- Long Backup Battery
- Heavy Load Capacity
- Fast Charging
- All Weather Body

HIGH LOAD LOADER
Driver + 500 KG Capacity

TECHNICAL SPECIFICATIONS

Variant	ZEOPLUS SPEED	ZEOFINE DELUXE, ZEOPLUS LOADER
Vehicle Category	L5 (D+6)	L3 Passenger, Loader,
Loading Capacity	600 kgs	400 Kgs
Vehicle Dimensions and Weight		
Length(mm)	3310	2790
Width(mm)	1485	990
Height(mm)	2180	1790
Ground Clearance (mm)	205	180
Wheel Base(mm)	2195	2140
GVW (kgs)	1185	784
Kerb Weight (kgs)	585	309
Cargo Size (Cu.Ft)	145	NA
Turning Radius	3.5	2.8
Chassis	Cr Tubes	CR Tubes
Tyre Size(Inch)	4*12	4*12
Performance		
Running Distance (km)	Upto 200km*	Upto 150km*
Top Speed (KmpH)	38	25
Gradibility (%)	19	18
Battery		
Operating Voltage (V)	51.2	60
Battery Energy (kWh)	10.75	6.24
Battery Connection	Single	5 Batteries
Capacity (Ah)	205	140
Battery Type	Li-on / LFP	Lead Acid / Li
Charging Time (Hours)	3-5 hours	6-8 hours
Drivetrain		
Transmission Type	Direct Coupler with Motor Manual (Manual dual speed)	Differential Direct Coupling with Motor
Motor type	PMSM DC Motor	BLDC Motor
Control Principle	Open Loop	Open Loop
Voltage Range	42V to 58V	40V to 56V
Peak Current	120 ± 15A	40 ± 15A
Suspension & Brakes		
Front Suspension	Coil spring with Independent Telescopic Shock Absorber	Dual Telescopic Shock Absorber
Rear Suspension	Leaf spring with Independent Telescopic shock Absorber	Leaf Spring with Telescopic Shock Absorber
Parking Brake	Mechanical Type	Mechanical Type
Front & Rear Brakes	Drum brake	Drum Brake

ZEOFINE



Zeoplus Axis India Pvt. Ltd.

Drive the Future with Electric Power

ICAT Innovation + Service + Excellence

MAKE IN INDIA

FINANCE FACILITY AVAILABLE PAN INDIA

AKASA FINANCE
Formerly known as Pooja Finelease Ltd

LIFL

लोकसुविधा LokSuvidha

MUFIN

TRIWHEELS
FINTECH SERVICES

Perfect Capital
Business finance made simple

PAISALO
EASY LOAN आसान लोन

PHF

CONTACT WITH US

CONTACT NO.: +91 8826002256, +91 8588880948,

https://www.zeofine.in/

Location:
Plot No. 62, Sector 16, Hsidc Industrial Area,
Bahadurgarh Haryana 124507